



HJ-DF1



SRD-33

产品型号 Model	HJ-DF1 / SRD-33	
喷头型号 Print head Model	理光GEN5/GEN6 喷头 Ricoh Gen5 / Gen6 printhead	
喷头数量 Number of printhead	4 头 4 色 4 head 4 color 6 头 6 色 6 head 6 color 8 头 8 色 8 head 8 color	
打印机工作模式 Operating mode of printer	①两组喷头双面同步数码打印 two head modules printing at both side of fabric at the same time ②可以仅仅使用单组喷头对面料单面喷印 can print on one side of fabric with single head module only	
打印精度与速度 Printing Precision and speed	High Precision Model 2pass (600*600dpi): 28m ² /h 3pass (600*900dpi): 21m ² /h 4pass (600*1200dpi): 14m ² /h	
最大打印宽度 Maximum printing width	HJ-DF1 1800mm	SRD-33 1600mm
打印材料 Printing Media	棉, 真丝, 羊毛, 麻, 化纤 (所有无弹性面料) cotton, silk, wool, linen (all kind fabric without tension)	
墨水类型 Ink type	活性墨水, 酸性墨水, 分散直喷墨水或其他 Reactive Ink, Acid Ink, Disperse Direct printing Ink, etc...	
墨水颜色 Ink color	可装4色/6色/8色 (with 4/6/8 color)	
喷头清洗方式 Print head Cleaning	自动碰头清洗 Automatic PH cleaning	保湿系统 Moisturizing system
可放入面料最大直径 Maximum diameter for fabric	450mm	
数据传输 Data transmission	TCP/IP网络接口 TCP/IP Network interface	
RIP软件 RIP Software	NeoStamp	
烘干方式 Drying system	打印前烘干&打印后烘干, 可同时使用也可分开使用, 温度可根据不同面料和湿度调节 drying before and after printing, can working separately or working at the same time , temperature can be adjusted as per the fabric and humidity	
电源 Power supply	HJ-DF1 AC380V & AC220V	SRD-33 AC220V
功率 Votage	18KW	10KW
打印机尺寸 Printer Dimension	HJ-DF1: L4026mm * W1600mm * H2000mm SRD-33: L2920mm * W980mm * H1600mm	
机器重量 Weight	2200KG	800KG
工作气压 Working pressure	0.6MPA	
工作环境 Working environment	温度 Temperature 20-30°C, 湿度 Humidity 50%-80%	