

| 项目 Item | 参数 Parameter | | | | | | | | |
|---|---|--------------------|--------------------|---------------|---------------|---------------|---------------|----------------|----------------|
| 喷头型号 / Head model | Epson 1600 1 pcs | | | | | | | | |
| 墨水类型 / Ink type | Pigment Ink KCMY | | | | | | | | |
| 打印精度/速度 (最大尺寸打印速度, 不含发色时间) Printing accuracy/speed (Maximum size printing speed, excluding color development time) | <table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">直径 / diameter 80mm</td> <td style="width: 50%; border: none;">直径 / diameter 60mm</td> </tr> <tr> <td style="border: none;">600*600 / 72s</td> <td style="border: none;">600*600 / 58s</td> </tr> <tr> <td style="border: none;">600*900 / 85s</td> <td style="border: none;">600*900 / 69s</td> </tr> <tr> <td style="border: none;">600*1200 / 99s</td> <td style="border: none;">600*1200 / 80s</td> </tr> </table> | 直径 / diameter 80mm | 直径 / diameter 60mm | 600*600 / 72s | 600*600 / 58s | 600*900 / 85s | 600*900 / 69s | 600*1200 / 99s | 600*1200 / 80s |
| 直径 / diameter 80mm | 直径 / diameter 60mm | | | | | | | | |
| 600*600 / 72s | 600*600 / 58s | | | | | | | | |
| 600*900 / 85s | 600*900 / 69s | | | | | | | | |
| 600*1200 / 99s | 600*1200 / 80s | | | | | | | | |
| 打印尺寸 Print size | 两种模具任意切换, 直径 80mm x 长度 450mm , 直径 60mm x 长度 450mm Two types of molds can be switched freely, with a diameter of 80mm x length of 450mm and a diameter of 80mm x length of 450mm | | | | | | | | |
| 工作模式 Working mode | 螺旋式打印 Spiral printing | | | | | | | | |
| RIP | neoStampa | | | | | | | | |
| 电脑配置 Computer configuration | Intel i5/7-10 代以上, 16G 内存, 千兆网口 Intel i5/7-10 and above, 16GB memory, Gigabit Ethernet port | | | | | | | | |
| 附件 /Enclosure | 加热罩壳 Heating cover shell | | | | | | | | |
| 功率 / power | AC 220V 2500W | | | | | | | | |
| 机器尺寸 / Machine size | 79cm X 40cm X 31cm | | | | | | | | |
| 工作环境 work environment | 湿度 / humidity 50%-80% 温度 / Temperature 20-30°C | | | | | | | | |

